



PROTECTAPEEL
PROTECTAPEEL
 PAINT • PROTECT • PEEL

Glasstrip Original

Protectapeel Glasstrip Original is a weather resistant strippable protective coating for protecting glass and other substrates used within the construction industry. The skin tight 'plastic' film will offer resistance to abrasion and overspray of solvent paints and rendering during the construction process for periods of up to 6 months.

Glasstrip may also be used to 'opaque' glass windows for a temporary period and also to protect any other sensitive, non-porous surfaces such as tiles, work surfaces, stainless steel and cladding.

The product is specially formulated to provide good UV resistance.



COLOUR - Transparent blue as standard, to allow light. Can be made opaque in specified colours to "blank out".

HEALTH & SAFETY - The compound is water-borne, non-toxic and non-flammable in the wet state. The dry film can be disposed of as low hazard. Please see separate Health & Safety Data.

USE - Strippable coating for masking and protecting glass windows and all non porous surfaces including PVC, metals and painted surfaces.

APPLICATION- By LAMBSWOOL ROLLER apply 2 coats (allowing first to tack off). **Apply generously to achieve a minimum dry film thickness of 100 microns (0.1mm).** BY SPRAY with Airless spray using 17 thou tip size and 2 box coats spray pressure 2500psi(150 Bar) **Do not apply in wet or freezing conditions and protect from rain for 48 hours after application.**

REPAIR - If the Spraylat film rips, the flap may be lifted and resealed by applying a fresh wet coat to the underside

and resealing. Alternatively, cut away and re-apply fresh coating – it will bond to itself.

EXTERNAL WEATHER RESISTANCE - Glasstrip original is suitable for up to 6 months exposure.

DRYING TIME- A dry film thickness of 0.1mm will be tack free in approximately 2 hours at room temperature. Force drying may be used by restricting the surface temperature to 50°C and using maximum air circulation possible.

REMOVAL - The dry film can be easily removed either by hand stripping or by pressure hose. Do not remove in freezing conditions as the film may be brittle

COVERAGE - One litre/kilo will cover about 4 Sq M at a film thickness of 0.1mm (0.004").

STORAGE - Shelf life 12 months. Store at temperatures between 5°C-25°C. **DO NOT ALLOW LIQUID TO FREEZE.**

CLEAN DOWN - Clean brushes or rollers in water immediately after use.

GENERAL NOTE: It is important that this product is thoroughly evaluated under production conditions before being commercially adopted (Such an evaluation should incorporate a reference to ageing). The above recommendations are made in good faith for the guidance of users and are without liability. Any queries should be referred to our Technical Sales Department.

SPRAYLAT
INTERNATIONAL

1 Bardsley Road, Earlstrees Industrial Estate, Corby,
 Northamptonshire. NN17 4AR

Tel: +44(0)1536 408409 Fax: +44(0)1536 400410

Web: www.spraylat.co.uk E-mail: enquiries@spraylat

